

## Declaration of Performance

No.: DOP\_HBT\_BSH

1. Unique product type identification code:

**Glued Laminated Timber HBT**

2. Intended use of the building product according to harmonized technical specification:

**Buildings and Bridges**

3. Name, registered trade name or brand, along with the address of the producer according to Article 11 Paragraph 5 construction products regulation:

**HASSLACHER Holzbauteile GmbH & Co. KG**  
**Am Hundsrück 2**  
**63924 Kleinheubach**  
**Germany**

4. Name and address of the authorized agent for the tasks referred to in Article 12 Paragraph 2 construction products regulation:

**No authorized agent**

5. System of assessment and verification of performance constancy pursuant to Appendix V of the construction products regulation:

**System 1**

6. If the building product is regulated by a harmonized standard:

**EN 14080:2013**

7. Notified Body(ies):

**No. 0672**

8. If the building product is regulated by an European technical assessment:

**Not applicable**



9. Declaration of performance:

Main Features and Characteristics		Performance
<b>Mechanical characteristics of glued laminated products</b>	Characteristics of timber	NPD
	Bending strength	Classification based on the characteristics of laminations according EN 338 – assignment of strength class corresponding Table 4 or 5 EN 14080 Spruce/Fir: GL20h, GL20c, GL22h, GL22c, GL24h, GL24c, GL28h, GL28c, GL30h, GL30c, GL32h, GL32c Larch: GL24h, GL24c, GL28h, GL28c
	Compression strength	
	Tensile strength	
	Shear strength	
	Modulus of elasticity	
	Bonding strength	
	Strength of finger joints	
	Additional for glued laminatd timber with large finger joints: Bending strength of large finger joints	
Geometrical data	NPD	
<b>Resistance to fire</b>		NPD
<b>Bonding strength</b>	Glue line integrity of surface bonding	Delamination test according EN 14080, Annex C, Test method B
	Glue lines between components of glued laminated timber	NPD
	Large finger joints	NPD
<b>Reaction to fire</b>		D-s2, d0
<b>Emission of formaldehyde</b>		E1
<b>Release of other dangerous substances</b>		NPD
<b>Durability of bonding strength</b>	Species	Spruce/Fir/Larch
	Adhesive finger joint	PUR / Typ I according EN 15425
	Adhesive surface bonding	MUF / Typ I according EN 301 I 90 GP 0,3 S
<b>Durability against biological attack</b>	Lamination without preservative treatment	Durability class 5 according EN 350-2
	Lamination with preservative treatment	NPD

NPD – No Performance Determined



10. The performance of the previous product corresponds with the declared performance/the declared performances. For the creation of this performance in accordance with the EU regulation No. 305/2011 the manufacturer is uniquely responsible for.

Signed in the name of the manufacturer:

Georg Dürregger / managing director HASSLACHER Holzbauteile GmbH & Co. KG

Name and position

**HASSLACHER Holzbauteile  
GmbH & Co. KG**  
Am Hundsrück 2 | 63924 Kleinheubach  
Germany | [hasslacher.com](http://hasslacher.com)  
T +49 9371 40 03-0  
Ein UNTERNEHMEN der HASSLACHER Gruppe  
A MEMBER of HASSLACHER group



**HASSLACHER  
NORICA TIMBER**  
From wood to wonders.

Kleinheubach, 12th June 2018

Place and date of issue

Stamp/signature

